



GIGA X8c Professional: Specifications

JURA Standards

| | |
|--|------------|
| Variable brewing chamber | 5 - 16 g |
| Intelligent Pre-Brew Aroma System (I.P.B.A.S.®) | Yes |
| Intelligent preheating | Yes |
| Active bean monitoring | Yes |
| Energy Save Mode (E.S.M.®) | Yes |
| High-performance pump, 15 bar | 3 |
| Thermoblock heating system | 3 |
| Fluid system | 2 parallel |
| Monitored drip tray | Yes |
| Maintenance status display | Yes |
| Integrated rinsing, cleaning and descaling programme | Yes |
| Adjustable water hardness | Yes |
| One or two cups of espresso in one brewing operation | Yes |
| JURA hygiene: TÜV-certified | Yes |
| CLARIS water-filtering system | Yes |
| Zero-Energy Switch or power switch | Classic |
| Swiss made | Yes |

Coffee specialities

| | |
|---|--|
| No. of individually programmable specialities | 29 |
| Preparation at the touch of a button | <ul style="list-style-type: none"> 1 Americano 2 latte macchiati 1 latte macchiato 2 cappuccini 1 cappuccino 2 caffè latte 1 caffè latte 2 coffees 1 coffee 2 espressi macchiati 1 espresso macchiato 2 espressi 1 espresso 2 ristretti 1 ristretto Pot of coffee Milk, milk foam |
| Pot of espresso-quality coffee | Yes |
| Hot water function | Power hot water system |
| Additional preground coffee powder | Yes |
| Pot of coffee (360 ml) | 1 min. 55 sec. (Speed) |
| 2 latte macchiati | 1 min. 8 sec. (Speed) |
| 2 cappuccini | 1 min. (Speed) |
| 2 caffè latte (cafés au lait) | 1 min. 5 sec. |
| 2 coffees | 38 sec. (Speed) |
| 2 espressi | 27 sec. (Speed) |
| 2 ristretti | 26 sec. |
| Hot water (200 ml) | 28 sec. |

Advantages

| | |
|---|--|
| JURA fine foam technology | Yes |
| Milk or milk foam preparation | Yes |
| Grinder type | Electrically adjustable ceramic disc grinder |
| Number of grinders | 2 |
| Powder chute for ground coffee | Yes |
| Powder recognition for additional ground coffee variety | Yes |
| A la carte bean selection | Yes |

Settings and programming options

| | |
|--|----------|
| Programmable amount of water | Yes |
| Amount of water can be adjusted for each preparation | Yes |
| Programmable coffee strength in levels | 5 |
| Coffee strength can be adjusted for each preparation | Yes |
| Programmable brewing temperature | 3 |
| Programmable amount of milk | Yes |
| Hot water temperature can be programmed | 3 levels |
| Programmable amount of hot water | Yes |
| Rotary Switch | Yes |
| Programmable preparation buttons | 8 |
| Produktname individualisierbar | Yes |

| | |
|--|-----|
| Resettable day counter | Yes |
| Programmable switch-on time | Yes |
| Programmable switch-off time | Yes |
| Switch-on and switch-off times can be specified for each day of the week | Yes |
| Shows the number of preparations for each individual product | Yes |
| Resettable cup counter | Yes |
| Water filter display | Yes |
| Integrated cappuccino rinsing and cleaning programme | Yes |
| Automatic milk rinse | Yes |
| Remaining time display / Progress bar | Yes |
| Generating code groups | Yes |
| Wireless ready | Yes |

Design and materials

| | |
|--|-------------------|
| Display | TFT color display |
| Venti Ports | Yes |
| Width-adjustable dual spout | 20 - 50 mm |
| Height-adjustable dual spout (Milk/Coffee) | 70 - 159 mm |
| Hot-water spout | Yes |
| Height-adjustable hot water spout | 69 - 165 mm |
| Cup illumination | White and amber |
| Indicator light for bean container | Yes |

| | |
|-----------------------------------|-----|
| Separate water tank for descaling | Yes |
| Sound design | Yes |
| Integrated storage compartment | Yes |

Areas of use and recommended maximum daily output

| | |
|----------------------------------|------------------------------|
| Recommended maximum daily output | 180 |
| Areas of use | Service provider Reseller |

Scope of delivery

| | |
|----------------|-----|
| Drip drain set | Yes |
|----------------|-----|

In figures

| | |
|--|-------------------------------|
| Coffee grounds container (servings) | 40 |
| Numbers of bean containers | 2 |
| Capacity of bean container with aroma preservation cover | 650 g |
| Cable length | 1.1 m |
| Voltage | 220 - 240 alternating current |
| Current | 10 amp |
| Frequency | 50 hz |
| Power | 2300 Watt |
| Permanent water connection | integrated (G 3/4") |
| Drip drain pipe | DIN15 |

| | |
|--------------------|------------|
| Accounting systems | compatible |
| Stand-by power | < 0.5 |
| Weight | 22 kg |
| Width | 32 cm |
| Height | 56.5 cm |
| Depth | 49.7 cm |
| Conformity mark | |
| Article Number | 13724 |